



**TDIP** : Precision ground double-ended inserts for Internal & external Turning and grooving

Designation	SSC Seat size code	CW	RE	BW	CDX	ft (min)	ft (max)	ap (min)	ap (max)	fg (min)	fg (max)	Grade & Vc
TDIP 1.00- 0.10	2	1.00	0.10	1.6	1.60	0.00	0.00	0.00	0.00	0.01	0.03	<a href="#">TT9080</a>
TDIP 1.00- 0.50	2	1.00	0.50	1.6	1.60	0.00	0.00	0.00	0.00	0.01	0.04	<a href="#">TT9080</a>
TDIP 1.20- 0.00	2	1.20	0.00	1.6	1.80	0.00	0.00	0.00	0.00	0.01	0.03	<a href="#">TT9080</a>
TDIP 1.40- 0.00	2	1.40	0.00	1.6	2.00	0.00	0.00	0.00	0.00	0.02	0.04	<a href="#">TT9080</a>
TDIP 1.50- 0.10	2	1.50	0.10	1.6	2.00	0.00	0.00	0.00	0.00	0.02	0.04	<a href="#">TT9080</a>
TDIP 2.00E- 0.10	2	2.00	0.10	1.6	-	0.05	0.07	0.20	0.60	0.03	0.05	<a href="#">TT9080</a>
TDIP 2.00E- 0.20	2	2.00	0.20	1.6	-	0.05	0.07	0.20	0.60	0.03	0.05	<a href="#">TT9080</a>
TDIP 2.00E- 1.00 Full radius insert	2	2.00	1.00	1.6	-	0.08	0.12	0.00	0.60	0.04	0.07	<a href="#">TT9080</a>
TDIP 2.15E- 0.15	2	2.15	0.15	1.6	-	0.06	0.08	0.20	0.60	0.04	0.06	<a href="#">TT9080</a>
TDIP 2.50E- 0.20	3	2.50	0.20	2.4	-	0.07	0.09	0.20	1.10	0.04	0.07	<a href="#">TT9080</a>
TDIP 3.00E- 0.20	3	3.00	0.20	2.4	-	0.11	0.14	0.30	1.30	0.05	0.09	<a href="#">TT9080</a>
TDIP 3.00E-	3	3.00	1.50	2.4	-	0.13	0.20	0.00	1.50	0.05	0.11	<a href="#">TT9080</a>

